

# S-ECRET LED

álmennyezeti LED mélysugárzó  
recessed LED downlights



TRIDONIC



## Alkalmazás:

Az S-ECRET-LED kerek süllyesztett LED álmennyezeti lámpatest. Alkalmazható álmennyezetbe süllyesztve lakásban irodában folyosón konyhában kirakat világításához stb.

Mozgásérzékelővel és lépcsőházi automatával is kapcsolható Nagy hatékonyságú LED alkalmazásával alacsony teljesítmény-felvétel.

## Műszaki adatok:

Védettség: IP20 / IP44 (álmennyezet alatt „-IP44” kivitel)  
Élettartam: 30 000 óra L70/B50  $T_{a_{max}}=40^{\circ}C$   
LED: Tridonic mélysugárzó modul  
Mélyhúzott alu lámpatestház horganyzott acél rugó műanyag véggel alu öntvény karika  
Régépített LED tápegység  
Fényes mintázott alu reflektor vagy PMMA opál diffúzer






## Application:

The S-ECRET LED lighting fixtures are circular-shaped recessed fitting. Mounted into the ceiling with Flats offices corridors kitchens shop-windows etc.

Suitable for switching with movement detector and timer  
The use of high efficiency LEDs grants very low overall consumption.

## Technical features:

Protection Degree: IP20 / IP44 (under ceiling “-IP44” types)  
Lifetime: 30 000 h L70/B50  $T_{a_{max}}=40^{\circ}C$   
LED: Tridonic downlight module  
Deep-pressed aluminum body galvanized steel springs with plastic ends die-cast aluminum ring  
LED driver built on top of fitting  
Glossy aluminum reflector or opal PMMA diffuser



Típus Type	Teljesítmény Power	Optika Optic	Méret Dimension
S-ECRET LED 1000-D60-3	11 6W / 1020 lm / 3000K	refl. 60°	Ø120x75mm Kivágás / cutout: Ø100mm
S-ECRET LED 1000-D60-4	11 6W / 1070 lm / 4000K		
S-ECRET LED 1000-D90-3	11 6W / 1020 lm / 3000K	refl. 90°	
S-ECRET LED 1000-D90-4	11 6W / 1070 lm / 4000K		
S-ECRET LED 1000-IP44-3	11 6W / 880 lm / 3000K	opal IP44	Ø170x85mm Kivágás / cutout: Ø140mm
S-ECRET LED 1000-IP44-4	11 6W / 920 lm / 4000K		
S-ECRET LED 2000-D60-3	22 7W / 2040 lm / 3000K	refl. 60°	
S-ECRET LED 2000-D60-4	22 7W / 2140 lm / 4000K		
S-ECRET LED 2000-D90-3	22 7W / 2040 lm / 3000K	refl. 90°	
S-ECRET LED 2000-D90-4	22 7W / 2140 lm / 4000K		
S-ECRET LED 2000-IP44-3	22 7W / 1760 lm / 3000K	opal IP44	
S-ECRET LED 2000-IP44-4	22 7W / 1840 lm / 4000K		

Dekoratív bővítő keret Widening frame	Méret Dimension	Kivágás Cutout
S-ECRET LED WR-1000	Ø180x40mm	Ø140mm
S-ECRET LED WR-2000	Ø230x40mm	Ø195mm